



ViewBoard® IFP33

Overview

The ViewBoard IFP33 Series is a versatile classroom solution that harmonizes a touch display with the myViewBoard software. Offering advanced lesson delivery options, the ViewBoard IFP3 Series helps teachers deliver engaging lessons and provides powerful device management tools for administrators.



Intuitive User Interface

The collapsible toolbar offers seamless access to controls, ensuring a smooth presentation flow.



Preinstalled myViewBoard Suite



myViewBoard suite enhances lesson delivery and administration with Whiteboard, Display, and Manager.



USB-C One Cable Solution

USB-C port empowers instant sharing, touch control, and 65W charging.



Enrich Learning with Multitasking

Watch videos in a floating window or split-screen while demonstrating work alongside questions.



Pen-on-paper Experience

Ultra-Fine Touch technology with 40 touchpoints and dual-pen tip support provides a natural writing experience.



Immersive Front Facing Speakers

Built-in front facing speakers deliver profound audio experiences.

Available Accessories



VB-STND-009



VPC37-W53-G1



VB-WIFI-004

Specifications

IFP6533-G

IFP7533-G

IFP8633-G

Panel Size
Panel Type
Display area (mm)
Aspect Ratio
Resolution
Colors
Colors
Contrast Ratio
Response Time
Viewing Angles
Backlight Life
Surface Treatment
Orientation
Processor:
RAM
Storage
Type/ Tech
Touch Point
HDMI (Input)
RGB / VGA (Input)
Audio (Input)
RS232 (Input)
OPS (Input)
WiFi (Input)
HDMI (Output)
Audio (Output)
SPDIF (Output)
RJ45
USB Type A
USB Type B
USB Type C
Speakers
Top Camera Plate
Embedded OS
Basic Annotation Software
Pro Annotation Software
Wireless Presentation
All-in-one USB port
Simple LAN sharing between IFP and slot-in device
Light Sensor
Voltage
Consumption
Wall Mount (VESA®)
Temperature (° C)
Humidity
Physical (inch / mm)
Packaging (inch / mm)
Net (lb / kg)
Gross (lb / kg)
Regulations
Package Contents
Compatible Slot-in PC

65 inches	75 inches	86 inches
TFT LCD Module with DLED Backlight. IPS		TFT LCD Module with DLED Backlight. VA
1428.48(H) × 803.52(V)	1649.664(H) × 927.936(V)	1913.04(H) × 1083.96 (V)
16:9		
UHD 3840x2160 (Pixels)		
1.07B colors		
400 nits		
5000:1 (max. with DCR enabled)		
8 ms		
H=178, V=178		
50,000 Hours (Min.)		
Hardness: 9H Anti-glare coating		
Landscape		
Quad-core ARM Cortex (A55*4)		
8GB DDR4		
128 GB		
Ultra Fine Touch Technology		
40 points touch		
HDMI-IN 2.0 x 3 (3840x2160 @60Hz)		
x1		
x1		
x1		
x1 (Optional Intel Standard OPS)		
x1 (Optional VB-WIFI002/VB-WIFI-004/VSB-050)		
HDMI 2.0 x1		
x1		
x1		
x2		
USB3.0:Front x2, Rear x2; USB2.0 x1		
x2 (Rear x1 + Front x1)		
Front*1 (PD65W + DP1.2 + Data USB2.0 + 10M/100M sharing)		
16W x 2		
Yes		
Android 11		
myViewBoard Whiteboard		
myViewBoard for Windows (Embedded in optional Windows Slot-in PC)		
myViewBoard Display		
(combine slot-in PC/Android/HDMI USB port) Front “SmartPort™ USB” to all channels.		
10/100M for Android & Slot-in PC		
Yes		
100-240V AC		
On:99W ; Off: ≤ 0.5W	On:106W ; Off: ≤ 0.5W	On:154W ; Off: ≤ 0.5W
800*400	600*400	800*600
0°C to 40°C		
20% ~ 80% RH noncondensing		
1488 x 897 x 88 mm / 58.6 x 35.3 x 3.5 in	1709 x 1020 x 88 mm / 67.3 x 40.2 x 3.5 in	1957 x 1160 x 100 mm / 77 x 45.7 x 3.9 in
1628x1005x208 mm / 64.1x 39.6x 8.2in	1863 x 1140 x 225 mm / 73.3x 44.9 x 8.6 in	2110 x 1283 x 225 mm /83 x 50.5 x 8.9 in
77.1lb/34.95kg	104.3lb/47.3kg	129.1lb/58.55kg
98.5 lb/44.7kg	133.5lb/60.55kg	167.3lb/75.9kg
FCC/ICES003, EPEAT, CE EMC, LVD or CB, RoHS Green BOM, & RoHS DoC, ErP, REACH SVHC List, & DoC, EEL, WEEE, BSMI,BIS		
1. 3m power cord by ship area 2. Remote control with AAA battery 3. 3m touch USB cable 4. Touch pen x 2 (VB-PEN-009) 5. Quick Start Guide + Compliance statement 6. RS232 adapter 7. Clamp x 5 8. Camera Plate 9. Screw x 8 (camera 2+2, wall mount 4) 10. HDMI cable 3m		
VPC2-O series/VPC2-O-1B series/VPC12-WPO-15/16		



PROJECTORS



PA503XE
4,000 Lumens XGA Business
Projector

22,000:1 contrast ratio
SuperColor™ technology
5 colour modes
Auto power off
Vertical keystone



PA700X
4,500 ANSI Lumens XGA
Business/Education Projector

12500:1 contrast ratio
Dual HDMI ports, USB Type-A port
Screen mirroring for smart devices
via USB
SuperColor™ Technology
1024x768 Native Resolution



PG603X
3,800 ANSI Lumens XGA Business
Projector

22,000:1 contrast ratio
Integrated USB
Screen mirroring for smart devices
via USB
LAN/WiFi display with vPresenter Pro
Horizontal and Vertical keystone



LS550WHE
3,000 ANSI Lumens WXGA Short
Throw LED Business/Education
Projector

3000000:1 contrast ratio
0.49 short throw ratio
5 colour modes
360° projection and H/V keystone
Comprehensive LAN control
Instant power on/off



LS610WHE
4,500 ANSI Lumens WXGA LED
Business/Education Projector

3rd generation LED technology
3,000,000:1 contrast ratio
60,000-hour light source life and less
power consumption
Wide color gamut
Instant power on/off, H/V keystone,
and LAN control



LS740HD
5,000 ANSI Lumens 1080p Laser
Installation Projector

3000000:1 contrast ratio
3rd generation laser phosphor
technology
Compact size and light weight
1.3x optical zoom, H/V keystone, 360°
projection, and portrait mode



LS921WU
5,000 ANSI Lumens 1080p Laser
Installation Projector

3000000:1 contrast ratio
3rd generation laser phosphor
technology
Compact size and light weight
1.3x optical zoom, H/V keystone, 360°
projection, and portrait mode