





Swiftpro® K65 Double Sided Retransfer Card Printer

The Swiftpro K65 retransfer card printer has an outstanding print quality for single and double sided printing. With 600dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalized physical and logical access management. The ultra-fast, powerful Swiftpro K65 printer is available with contact and contactless smart card encoding technologies and 120-card hopper capacity. The large color LCD panel can display multiple languages. This reliable and durable printer is the ideal solution for those who want to convert their printer to an IP printer without any extra modifications.

- ✓ FINANCIAL CARDS
- ✓ LICENCES AND GOVERNMENT IDS
- ✓ SCHOOL / COLLEGE IDS
- ✓ EMPLOYEE / CUSTOMIZED IDS



SECURITY

The ribbon erase function prevents leakage of personal information on the monochrome black panel ink ribbon. It scrambles information beyond recognition to protect this data.



VERSATILITY

Swiftpro's modular design permits customers to upgrade as their card programs need changes.



IMAGE QUALITY

High Resolution printing using 600dpi printing provides superior print quality for all your card programs.



RELIABILITY

Swiftpro K-Series are well respected globally for their Japanese engineering for quality and reliability.



INNOVATION

Innovating since the 90's with state of the art retransfer printers, providing safe, secure, and reliable ID card printer solutions to global organizations since 1989.



DURABILITY

Highly durable printers with industry leading warranties on all our products and lifetime on the print head.

Distributed by:

Geschaft Equipment Corporation



Swiftpro® K65 Double Sided



CORPORATE



EDUCATION



FINANCE



HEALTHCARE



RETAIL



TRANSPORT



GOVERNMENT

Printing

Dye Sublimation Retransfer

Full Color Retransfer printing

Single and Double Sided Printing

Fast Mode Print Speed: 24s per card, 150 cards per hour *average value of 1000 film images

Fast Mode Print Speed: 30s per card, 120 cards per hour *average value of 1000 film images

256 Gradation Printing

Over the Edge Printing on CR80, ID-1 Cards

Standard features

USB & Ethernet connectivity

120-Card Input Hopper (30mil)

120-Card Output Hopper (30mil)

Large, Color Liquid Crystal Panel Display

600 DPI Print Resolution

36 Month Printer Warranty

Lifetime Printhead Warranty

Microsoft Certified Drivers

Silicone Card Feed Roller for Reliable Card Input

Solenoid Electronic Lock for Card Input Hopper

Solenoid Electronic Lock for Supplies

Software-controlled Lock/Unlock, Status Monitor

K Ribbon Erase Function

IpSec Security Data Encryption IPv6 IPv4

Inline Bend Remedy

MAC Address Forced Printing (UV Panel on Card)

Reboot Function

Overcoat Function for Reusing Retransfer Film

Adjustable Card Ejection Speed (Display +1, 0, -1)

Kensington Lock

Encoding

Magnetic Stripe ISO High/Low Coercivity Encoder

Contactless Encoder, Omnikey 5127 (iClass, MIFARE and DESFire, Felica)

Contact Encoder (CF-7CRW / Control board)

Contact Encoder (CF-7CCS / IC Contact Station)

Software supported

All Card Personalizations software used through Swiftpro Driver*

*check with Software vendor, as some features may be limited for use on Swiftpro Printers

Microsoft® Windows® 10 32bit / 64bit

Microsoft® Windows® 11

Microsoft® Windows® Server 2016, 2019, and 2022

Swiftpro Genuine Color Ribbons

YMCK - 1000 Yield

YMCKK - 750 Yield

YMCKP Peel Off Ribbon - 750 Yield

YMCKU UV - 750 - Yield

InTM Retransfer Film - 1000 Yield

Physical Specification

Height 14.17 in (360 mm) Without Card Stacker

Width 13.6 in (346 mm) Without Card Stacker

Depth 12.83 in (326 mm) Without Card Stacker

Weight 30.86 lb (14.0 kg or less)

Mini PC Max. 220m x 208mm x 44mm (WxDxH)
Storage

Interface

USB 2.0 (Hi-speed / Full Speed) USB 2.0 (Hi-speed / Full Speed), USB HUB interface (Type A Connector) for Connection of External Optional Units

Ethernet (100BASE-TX / 10BASE-T)

Electrical

Temperature: 59°F to 86°F (15°C to 30°C)

Humidity: 35% to 70% (YMCK ink, No Condensation)

3.5A (110V system) 1.6A (220V system)

310W (maximum power when all options are installed)

Card specification

Card Thickness 10-40mil

Card Size ISO 7810 Format, CR80, ID-1

Card Material: PVC, PC, PET, PET-G

Technology Cards Contact and or Contactless with and Without Mag Stripe

Safety Standards

Agency Listing: UL, CE, FCC, KC, CCC, CSA



Security Erase



UV Printing

WEBSITE: www.geschafthcorp.com

LANDLINE: (8) 256 0569 or (8) 256 1766

ADDRESS: 3rd floor, 100-A Scout Dr. Lazcano St.,
Brgy. Laging Handa, Quezon City, Philippines

Geschafth
Equipment Corporation