




Swiftpro® K65 Double Sided Retransfer Card Printer

The Swiftpro K65 retransfer card printer has an outstanding print quality for single and double sided printing. With 600dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalized physical and logical access management. The ultra-fast, powerful Swiftpro K65 printer is available with contact and contactless smart card encoding technologies and 120-card hopper capacity. The large color LCD panel can display multiple languages. This reliable and durable printer is the ideal solution for those who want to convert their printer to an IP printer without any extra modifications.

- ✓ FINANCIAL CARDS
- ✓ SCHOOL / COLLEGE IDS
- ✓ LICENCES AND GOVERNMENT IDS
- ✓ EMPLOYEE / CUSTOMIZED IDS



SECURITY

The ribbon erase function prevents leakage of personal information on the monochrome black panel ink ribbon. It scrambles information beyond recognition to protect this data.



VERSATILITY

Swiftpro's modular design permits customers to upgrade as their card programs need changes.



IMAGE QUALITY

High Resolution printing using 600dpi printing provides superior print quality for all your card programs.



RELIABILITY

Swiftpro K-Series are well respected globally for their Japanese engineering for quality and reliability.



INNOVATION

Innovating since the 90's with state of the art retransfer printers, providing safe, secure, and reliable ID card printer solutions to global organizations since 1989.



DURABILITY

Highly durable printers with industry leading warranties on all our products and lifetime on the print head.

Distributed by:

Geschaft Equipment Corporation



Swiftpro[®] K65 Double Sided



CORPORATE



EDUCATION



FINANCE



HEALTHCARE



RETAIL



TRANSPORT



GOVERNMENT

Printing

- Dye Sublimation Retransfer
- Full Color Retransfer printing
- Single and Double Sided Printing
- Fast Mode Print Speed: 25s per card, 150 cards per hour *average value of 1000 film images
- Fast Mode Print Speed: 30s per card, 120 cards per hour *average value of 1000 film images

- 256 Gradation Printing
- Over the Edge Printing on CR80, ID-1 Cards

Standard features

- USB & Ethernet connectivity
- 100-Card Input Hopper (30mil)
- 100-Card Output Hopper (30mil)
- Large, Color Liquid Crystal Panel Display
- 600 DPI Print Resolution
- 36 Month Printer Warranty
- Lifetime Printhead Warranty
- Microsoft Certified Drivers
- Silicone Card Feed Roller for Reliable Card Input
- Solenoid Electronic Lock for Card Input Hopper
- Solenoid Electronic Lock for Supplies
- Software-controlled Lock/Unlock, Status Monitor
- K Ribbon Erase Function
- IpSec Security Data Encryption IPv6 IPv4
- Inline Bend Remedy
- MAC Address Forced Printing (UV Panel on Card)
- Reboot Function
- Overcoat Function for Reusing Retransfer Film
- Adjustable Card Ejection Speed (Display +1, 0, -1)
- Kensington Lock

Encoding

- Magnetic Stripe ISO High/Low Coercivity Encoder
- Contactless Encoder, Omnikey 5127 (iClass, MIFARE and DESFire, Felica)
- Contact Encoder (CF-7CRW / Control board)
- Contact Encoder (CF-7CCS / IC Contact Station)

Software supported

- All Card Personalizations software used through Swiftpro Driver*
- *check with Software vendor, as some features may be limited for use on Swiftpro Printers
- Microsoft® Windows® 10 32bit / 64bit
- Microsoft® Windows® 11
- Microsoft® Windows® Server 2016, 2019, and 2022

Swiftpro Genuine Color Ribbons

- YMCK - 1000 Yield
- YMCKK - 750 Yield
- YMCKP Peel Off Ribbon - 750 Yield
- YMCKU UV - 750 - Yield
- InTM Retransfer Film - 1000 Yield

Physical Specification

- Height 14.17 in (360 mm) Without Card Stacker
- Width 13.6 in (346 mm) Without Card Stacker
- Depth 12.83 in (326 mm) Without Card Stacker
- Weight 30.86 lb (14.0 kg or less)
- Mini PC Max. 220m x 208mm x 44mm (WxDxH)
- Storage

Interface

- USB 2.0 (Hi-speed / Full Speed) USB 2.0 (Hi-speed / Full Speed), USB HUB interface (Type A Connector) for Connection of External Optional Units
- Ethernet (100BASE-TX / 10BASE-T)

Electrical

- Temperature: 59°F to 86°F (15°C to 30°C)
- Humidity: 35% to 70% (YMCK ink, No Condensation)
- 3.5A (110V system) 1.6A (220V system)
- 310W (maximum power when all options are installed)

Card specification

- Card Thickness 10-40mil
- Card Size ISO 7810 Format, CR80, ID-1
- Card Material: PVC, PC, PET, PET-G
- Technology Cards Contact and or Contactless with and Without Mag Stripe

Safety Standards

- Agency Listing: UL, CE, FCC, KC, CCC, CSA



Security Erase



UV Printing

WEBSITE: www.geschafcorp.com
LANDLINE: (8) 256 0569 or (8) 256 1766
ADDRESS: 3rd floor, 100-A Scout Dr. Lazcano St., Brgy. Laging Handa, Quezon City, Philippines

Geschaf
Equipment Corporation